



## PRODUCT DESCRIPTION

ProFill™ is a siliconized acrylic tile caulk specially formulated for ease of use, durability and superior adhesion. Available in all 30 TilePro designer colors.

## AREAS OF USE

ProFill can be used to fill or repair joints around sinks, tubs and countertops. Can also be used to seal windows, door frames, vinyl siding and drywall. Maximum joint width 1/4".

## LIMITATIONS

This product contains colorants and may stain porous materials, like wallpaper and walls. Masking or shielding these areas may be necessary. Do not apply if temperatures fall below 50° F (10° C) or if rain or freezing temperatures are expected in the next 24 hours.

## SURFACE PREPARATION

Surface must be dry and free from dirt, oil and other contaminants that will prevent a good bond.

## MIXING

No mixing required. Use ProFill straight from the tube according to instructions.

## APPLICATION

- 1: Knead tube until soft.
2. Cut tip off at an angle.
3. Completely fill joints with caulking.
4. Smooth with wet finger.

## CURING

Full cure is reached in 48 – 72 hours. When applied in an area exposed to moisture, allow at least 12 hours of cure time before using water.

## CLEAN-UP

Clean hands and tools with water. Excess sealant can be cleaned up with a damp cloth or sponge.

## PACKAGING

- 10.2 FL. OZ. (305 ML) Tube
- 30 designer colors

## STORAGE

Store in a cool dry area. Keep from extreme heat or cold.

## SAFETY

Avoid eye contact. If eye contact occurs, flush with water for 15 minutes and call a physician. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.

## WARNING

Western States Wholesale, as blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components in this product, contains chemicals known to the State of California, to cause cancer, birth defects, or other reproductive harm.