



# ProGRAM

## GRANITE AND MARBLE MEDIUM-BED MORTAR

### PRODUCT DESCRIPTION

ProGram™ is specially formulated for installing granite, marble, natural stone, clay pavers, or any installation requiring a medium bed mortar. ProGram holds tiles in place immediately without slipping or sagging.

### AREAS OF USE

- Interior or exterior floors, walls, and countertops
- Concrete, mortar beds, masonry

### LIMITATIONS

Do not apply to wood, plywood, parquet, asphalt sheeting, vinyl wallboard, metal, glass, fiberglass or sponge-backed vinyl flooring. Do not use to install resin-backed stone. Do not install at thicknesses exceeding 3/4" (19 mm) or tiles may become dislodged.

### APPLICABLE STANDARDS

Meets or exceeds ANSI A118.4.

### SURFACE PREPARATION

Surface must be dry and free from dirt, oil and other contaminants that will prevent a good bond. Glossy or painted surfaces must be sanded and cleaned. Surface temperature must be between 50°F (10°C) and 100°F (38°C). Concrete must be fully cured before ProGram is applied.

### MIXING

Thoroughly mix 5 1/2 quarts (5.21 L) clean, cool water and a 50 lb. (22.68 kg) bag of ProGram mortar to a smooth, paste-like consistency. Let stand for 5–10 minutes, stir again and use. Stir occasionally to keep workable, but do not add more water. When properly mixed, troweled ridges will stand firm.

### APPLICATION

ProGram is intended to be used as a setting bed from 3/32" to 3/4" (2.4 mm to 19 mm) after the tiles have been embedded. Using the flat side of trowel, apply skim coat of mortar to the surface. Apply additional mortar with notched side of trowel held at a 45° angle to the surface, combing in one direction. Press tile firmly into place. Adjust tile promptly.

Do not spread more material than can be tiled in 15 minutes or while material is still sticky to the touch. If mortar dries, remove and replace with fresh material. Material in bucket will remain workable for up to 2 hours. Temperatures may vary working conditions.

### CURING

Allow to cure for a minimum of 24 hours before grouting, depending upon temperature and humidity.

### CLEAN-UP

Clean with soap and water.

### COVERAGE

35–45 sq. ft. per 50 lb. bag when applied with 1/2" X 1/2" square-notched trowel.

### PACKAGING

- 50 LBS. (22.7 KG) Bag
- White or Gray

### STORAGE

Store in a cool dry area. Keep from freezing.

### SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. This product contains free silica. Do not breathe dust; wear NIOSH approved respirator. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

### WARNING

Western States Wholesale, as blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components in this product, contains chemicals known to the State of California, to cause cancer, birth defects, or other reproductive harm.

### AVERAGE COVERAGE PER 50 LB. (22.7 KG) BAG

	1/4" X 1/4" (6.4 mm X 6.4mm)	1/4" X 3/8" (6.4 mm X 6.4mm)	1/2" X 1/2" (6.4 mm X 6.4mm)
Product	Square-notched Trowel	Square-notched Trowel	Square-notched Trowel
ProGram	77 Sq. Ft. (7.1 M <sup>2</sup> )	66 Sq. Ft. (6.1 M <sup>2</sup> )	40 Sq. Ft. (3.7 M <sup>2</sup> )

\* These measurements are approximate. Actual coverage may vary due to prevailing conditions.